Delfin Z22 ZFR EV AP 560 K4



€9,927

List price excl. VAT, for business customers. Freight and installation not included.

II 3D Ex h IIIC T80°C (int) / T135°C (ext) X Dc

Only for ATEX zone 22 areas and dust with a minimum ignition energy (MIE) above 3 mJ.

TECHNICAL DATA

Model	Smaller version Z22 ZFR EV AP 560 K2	Z22 ZFR EV AP 560 K4
PERFORMANCE		
Max. air flow	**2,500 m³/h**	**3,500 m³/h**
Max. negative pressure	**210 mmH2O**	**370 mmH2O**
Suction inlet	**Ø200 mm**	**Ø200 mm**
Power	**2.2 kW**	**4 kW**
Voltage, frequency	**400 V, 50 Hz**	**400 V, 50 Hz**
Current	**–**	**7.6 A**
FILTRATION		
Primary filter	**Star filter, polyester ANT M**	**Star filter, polyester ANT M**
Filter surface	**50,000 cm²**	**50,000 cm²**
Filter diameter	**Ø560 mm**	**Ø560 mm**
Secondary filter	**H14, standard**	**H14, standard**
Filter cleaning	**Manual shaker**	**Manual shaker**
MACHINE		
Container	**100 l**	**100 l**

Model	Smaller version Z22 ZFR EV AP 560 K2	Z22 ZFR EV AP 560 K4
Dimensions	**78 × 126 × 251 cm**	**78 × 126 × 251 cm**
Weight	**100 kg**	**130 kg**
Noise level	**72 dB(A)**	**74 dB(A)**
Protection rating	**IP55**	**IP55**
ATEX		
Marking	**II 3D Ex h IIIC T80°C (int) / T135°C (ext) X Dc**	**II 3D Ex h IIIC T80°C (int) / T135°C (ext) X Dc**
Permitted area	**ATEX zone 22**	**ATEX zone 22**
Item code	**Z22ZFREVAP560K4-001**	**Z22ZFREVAP560K4-001**
PRICE		
List price excl. VAT	**€9,927**	

Values from the Delfin manual Z22 ZFR EV AP 560 (EN), sections 2.4.1, 4.4 and 4.5. Where the price list, datasheet or Delfin's website differ, the manual applies. Weight, protection rating and H14 filter: Delfin price list 2026, p. 120. Current (K4): Delfin datasheet. Price: Delfin price list 2026, p. 120.

OPTIONS, FILTERS AND ACCESSORIES

What Delfin supplies for this model. Ask us for a price.

Description	Item code
MOTOR	
ATEX motor II 3GD IIIC, 230/400 V, 60 Hz	**–**
FILTRATION	
Absolute HEPA filter, 10 m² (included)	**H**
CONSTRUCTION	
AISI 304 stainless steel collection tank	**X**
AISI 304 stainless steel tank and filter chamber	**XX**
AISI 304 stainless steel filter chamber, collection tank, cover and frame	**XXX**
Earth grounding (included)	**MT**
CONTROL	
24 V remote control (with electrical panel if not installed)	**LOC REM**
ACCESSORIES	
Flanged reduction for flex hose, Ø200/200	**SL.2632.0200**
Flanged reduction for flex hose, Ø200/150	**SL.6882.0200**
Flanged reduction for flex hose, Ø200/120	**SL.3775.0200**

Description	Item code
Flanged reduction for flex hose, Ø200/100	SL.6883.0200
Flanged two-way branch, Ø200/150/150	SL.2775.0200
Flanged two-way branch, Ø200/120/120	SL.2692.0200
Flanged two-way branch, Ø200/100/100	SL.3022.0200
Articulated extraction arm with earth grounding, Ø100/Ø100	TA.0943.0000
Articulated extraction arm with earth grounding, Ø150/Ø150	TA.0177.0000
Articulated extraction arm with earth grounding, Ø150/Ø200	TA.1256.0000
Articulated extraction arm with earth grounding, Ø200/Ø200	TA.0511.0000
Flanged branch for articulated arms, Ø200/100/100	ESSL.2201.0200
Flanged branch for articulated arms, Ø200/150/150	ESSL.4703.0200

Source: Delfin price list 2026, p. 120, 121.

Ask us about this model
We advise on selection, sizing and zones. Call +45 70 23 12 03 or write to sales@particulair.com.

Reservations: we reserve the right to printing errors and other errors, to price changes not yet updated, and to technical data, designs and upgrades changed by the manufacturer without notice. Prices and data are indicative until confirmed in a written offer. Pictures may show optional equipment.