MOBILE DUST COLLECTOR · DEPURECO

Depureco DF 40

Dust collector for areas without an ATEX zone.

A mobile dust collector on swivel castors with brakes. 4 kW fan, star filter in class M and a manual filter shaker.



€5,712

List price excl. VAT, for business customers. Freight and installation not included.

TECHNICAL DATA

Model	DF 40
PERFORMANCE	
Inlet and max. air flow	**Ø150 mm – 1,500 m³/h, Ø180 mm – 2,100 m³/h, Ø200 mm – 2,700 m³/h**
Max. negative pressure	**370 | 340 | 270 mmH2O at Ø150 | Ø180 | Ø200**
Power	**4 kW**
Voltage, frequency	**400 V, 50/60 Hz**
FILTRATION	
Primary filter	**Star filter, class M, polyester, 45,000 cm²**
HEPA filter	**HEPA H13 option, 160,000 cm²**
Filter cleaning	**Manual shaker; SP available**
MACHINE	
Container	**Painted steel container, 65 l**
Dimensions	**630 × 1,100 mm, height 2,150 mm**
Weight	**145 kg**
Noise level	**73 dB(A)**
Protection rating	**IP55**

Model	DF 40
Item code	**A1102 (catalogue)**
PRICE	
List price excl. VAT	**€5,712**

Source: Depureco manual DF series (EN, rev. 01), Depureco data sheet and declaration of compliance, as compiled in our model list (8 October 2026). Where sources differ, the declaration and the manual apply. Price: Depureco price list 2026 (v. 1.1), p. 84.

OPTIONS, FILTERS AND ACCESSORIES

What Depureco supplies for this model. Ask us for a price.

Description	Item code
MOTOR	
Fan 460 V, 60 Hz, three-phase	–
FILTRATION	
HEPA H13 secondary filter (EN 1822-5)	**P12820**
Class M antistatic filter (38,000 cm²)	**ANT M**
Filter resistant to 250 °C	**NOMEX**
Class M PTFE filter (38,000 cm²)	**PTFE**
PTFE antistatic filter, class M (38,000 cm²)	**PTFE ANT**
FILTER CLEANING	
Automatic reverse jet filter cleaning, 4 antistatic polyester cartridges, 12 m²	**SP**
Pneumatic filter shaker	**PSC**
CONSTRUCTION	
AISI 304 stainless steel bin	**BX**
AISI 304 stainless steel bin and chamber	**GX**
AISI 304 stainless steel construction (fan excluded)	**TX**
Spark trap	**SPK**
Stainless steel fan	**FX**
Grounding	**GRD**
UL/CSA certification (on request)	**UL/CSA**
ACCESSORIES	
Flanged connection for flexible hose, Ø150 mm	**P12300/150**
Flanged connection for flexible hose, Ø180 mm	**P12300/180**
Flanged connection for flexible hose, Ø200 mm	**P12300/200**
Metal clamp, Ø150 mm	**P12359**

Description	Item code
Metal clamp, Ø180 mm	**P12360**
Metal clamp, Ø200 mm	**P12503**
Two-way flanged connection, Ø70–70 mm	**P12335/70**
Two-way flanged connection, Ø100–100 mm	**P12335/100**
Two-way flanged connection, Ø120–120 mm	**P12335/120**
Flanged connection for articulated arm, Ø150 mm	**P12334**
Articulated arm Ø150 mm, L = 3 m	**P12336**
Spare filter, class M	**P09120**
Spare cartridge filter, SP version (1 pc.)	**P09577**

Source: Depureco price list 2026 (v. 1.1), p. 84–85.

Ask us about this model
We advise on selection, sizing and zones. Call +45 70 23 12 03 or write to sales@particulair.com.

Reservations: we reserve the right to printing errors and other errors, to price changes not yet updated, and to technical data, designs and upgrades changed by the manufacturer without notice. Prices and data are indicative until confirmed in a written offer. Pictures may show optional equipment.