STATIONARY DUST COLLECTOR · DEPURECO

Depureco DF FIX 75

Dust collector for areas without an ATEX zone.

A stationary filter unit for central vacuum systems, with an electrical cabinet and forklift brackets. 7.5 kW fan and automatic filter cleaning (PSC).



€13,720

List price excl. VAT, for business customers. Freight and installation not included.

TECHNICAL DATA

Model	DF FIX 75
PERFORMANCE	
Inlet and max. air flow	**Ø200 mm – 3,900 m³/h**
Max. negative pressure	**575 mmH2O max., 539 mmH2O in continuous operation**
Power	**7.5 kW**
Voltage, frequency	**400 V, 50/60 Hz**
FILTRATION	
Primary filter	**Star filter, class M, polyester, 45,000 cm²**
HEPA filter	**HEPA H14 option**
Filter cleaning	**PSC: a pneumatic piston shakes the filter at fixed, adjustable intervals. Requires compressed air**
MACHINE	
Container	**Painted container 175 l on wheels**
Dimensions	**850 × 1,700 mm, height 1,920 mm**
Weight	**350 kg**
Noise level	**74 dB(A)**
Protection rating	**IP55**

Model	DF FIX 75
PRICE	
List price excl. VAT	**€13,720**

Source: Depureco manual DF FIX (EN, rev. 05), data sheet and declaration, as compiled in our model list (8 October 2026). Where sources differ, the declaration and the manual apply. Price: Depureco price list 2026 (v. 1.1), p. 86.

OPTIONS, FILTERS AND ACCESSORIES

What Depureco supplies for this model. Ask us for a price.

Description	Item code
FILTRATION	
HEPA H14 secondary absolute filter (EN 1822-5)	**P12829**
Class M antistatic filter (38,000 cm²)	**ANT M**
Class M PTFE filter (38,000 cm²)	**PTFE**
PTFE antistatic filter, class M (38,000 cm²)	**PTFE ANT**
FILTER CLEANING	
Automatic reverse jet filter cleaning, 4 antistatic polyester cartridges, 12 m²	**SP**
CONSTRUCTION	
AISI 304 stainless steel bin	**BX**
AISI 304 stainless steel bin and chamber	**GX**
Grounding	**GRD**
Remote control of the machine	**LR**
Remote control via wireless	**WRLS**
ACCESSORIES	
Flanged connection for flexible hose, Ø150 mm	**P12300/150**
Flanged connection for flexible hose, Ø180 mm	**P12300/180**
Flanged connection for flexible hose, Ø200 mm	**P12300/200**
Metal clamp, Ø150 mm	**P12359**
Metal clamp, Ø180 mm	**P12360**
Metal clamp, Ø200 mm	**P12503**
Spare filter, class M	**P09120**
Spare cartridge filter, SP version (1 pc.)	**P09577**
CONTROL PANEL	
Management of the discharge system of the filtration/collection unit	–
SP cleaning system control on the filter unit	–

Description	Item code
Remote control via wireless	WRLS
Pressure stabiliser and touch display	–
Management of the level sensor of the filtration/collection unit	–
Inverter (on request)	–

Source: Depureco price list 2026 (v. 1.1), p. 86–87.

Ask us about this model
We advise on selection, sizing and zones. Call +45 70 23 12 03 or write to sales@particulair.com.

Reservations: we reserve the right to printing errors and other errors, to price changes not yet updated, and to technical data, designs and upgrades changed by the manufacturer without notice. Prices and data are indicative until confirmed in a written offer. Pictures may show optional equipment.