

DEPURECO · II 3 D EX HTC IIIB T140 DC

Depureco CVS 200 Z22



The Depureco CVS 200 Z22 is a central ATEX vacuum unit for Zone 22 (external) -- delivered WITHOUT integrated filter and WITHOUT container. A 22-30 kW 3D ATEX-certified side-channel blower (top-mounted in a sound-insulated cabinet) delivers 1985 m³/h at 200 mBar vacuum and 74 dB(A). The unit **must** be mandatorily combined with a separate filtration and collection unit^{**} (DV AIR, DV AIR WB or HF Z22) -- the CVS alone is just the prime mover of the installation. Remote vacuum control, pressure-relief valve and inlet silencer (O130 connection to O70/100/130 hose via P12780) are included from the factory. An optional HEPA H14 secondary filter (110,000 cm² fiberglass) can be added. Footprint 821x1319 mm, height 1792 mm, IP55, insulation class F. Inlet O127 mm. This is the ****P-variant****: high airflow (1985 m³/h) and low vacuum (200 mBar) -- for large pipe networks with many take-off points, or large air volumes at moderate vacuum. If instead you have short pipes, heavy or moist products, or long suction lifts, see CVS 200 S Z22 (S-variant) at 380 mBar vacuum. ATEX marking II 3 D Ex htc IIIB T140 Dc.

APPLICATIONS

- Central vacuum unit for multiple take-off points in ATEX Zone 22
- Combined with separate filter unit for industry-specific filtration
- Long pipe runs in plant and process installations
- Continuous duty with tailored collection (big-bag, Longopac, rotary valve, container)

Technical specifications

ATEX marking	II 3 D Ex htc IIIB T140 Dc
Internal / external zone	- / 22
Motor type	3D ATEX-certificeret sidekanalblaeser, 22-30 kW (topmonteret i lyddaempet kabinet)
Airflow	1985 m ³ /h
Vacuum	200 mbar
Sound pressure	74 dB(A)
Filter class	No primary filter
Filter type	Intet primaerfilter paa enheden -- CVS Z22 skal kombineres med en separat filter- og opsamlingsenhed (fx DV AIR, DV AIR WB eller HF Z22). Valgfri HEPA H14 sekundaer (110.000 cm ² fiberglas, EN 1822 klasse H14) kan tilfoejes som option mellem pumpe og filter-enhed.
Primary filter	Intet -- kraever separat filter-enhed
Cleaning system	Ikke relevant paa enheden -- renses paa tilknyttet filter-enhed (SP pulsejet-rens paa fx DV AIR eller HF)
Collection system	No collection (separate filtration and collection unit required)
Material	Lakeret staal-kabinet med lyddaempning
IP class	IP55
Power	30.0 kW
Voltage	400 V / 50-60 Hz
Dimensions (L x W x H)	821 x 1319 x 1792 mm

Questions and answers

What does the ATEX marking II 3 D Ex htc IIIB T140 Dc mean?

The unit is EU-type approved under ATEX directive 2014/34/EU for operation in external Zone 22 (dust, low risk). 'Ex h' is the constructional safety type per EN ISO 80079-36/37, and 'tc' specifies the enclosure protection level against dust ignition. 'IIIB' covers non-conductive dust (paper, fibre, grain etc.) -- class IIIC (conductive metallic dust) requires separate approval. 'T140' is the maximum surface temperature in operation (140 degrees C). 'Dc' is the EPL code for Zone 22.

Why does CVS Z22 have no built-in filter or container?

CVS Z22 is designed as a modular central system. It contains only the vacuum unit -- motor and ATEX side-channel blower in a sound-insulated cabinet -- without filter and without container. That gives freedom to tailor the rest of the installation to the process: the filter is chosen for the dust type (class M, H13 or H14), and the collection is chosen for the duty cycle (continuous discharge via big-bag or Longopac, rotary valve + container, or integrated container as on DV AIR WB). The catalogue states it directly: 'CVS vacuum units must be mandatorily combined with a filtration and collection unit' -- CVS is the prime mover, and the filter/collection unit is the other half of the solution.

Which filter units can CVS Z22 be combined with?

Three main options: (1) **HF Z22** series -- central-system filter without container, where dust is discharged continuously via big-bag, Longopac, rotary valve or direct pipe to process. Suits when bin emptying isn't practical. (2) **DV AIR** / **DV AIR Z22** -- large-format filter unit (1700 or 2700 m³/h, 4 or 7 cartridges) without integrated container, combined with DISCHARGE SYSTEMS (flaps, rotary valve, butterfly) or a pre-separator (FILTER HOPPER). (3) **DV AIR WB** / **DV AIR WB Z22** -- filter unit with 175 L integrated stainless-steel container. We help match the filter unit to your CVS model based on airflow, vacuum and discharge needs.

What is the sweet spot for Depureco CVS 200 Z22?

Depureco CVS 200 Z22 delivers 1985 m³/h at 200 mBar vacuum with O127 mm inlet. Power class is 22-30 kW. Choose it when the pipe network pressure drop and the number of take-off points match this profile -- see the model comparison on the category page to put all six CVS variants side by side.

Contact and advisory

PARTICULAIR

Particulair

Højtoften 12

2690 Karlslunde, Denmark

CVR: 34129894

Phone: (+45) 70 23 12 03

E-mail: sales@particulair.com

Web: particulair.eu

Product page: particulair.eu/ex-vac/en/atex-dust/cvs-200-z22/

SMARTER THINKING • BETTER WORKING

This datasheet is generated deterministically from Particulair product data. Prices and availability provided on request. All specifications subject to change without notice.