

## ACCESSORIES

# CLAMP 210 BRIDGE

Bridge clamp with plastic bridge for externally corrugated spiral hoses



CLAMP 210 BRIDGE is a bridge clamp developed for externally corrugated spiral hoses. The special feature is the plastic bridge made of PA6 W1 - a glass-fibre-reinforced polyamide that provides electrical insulation and secure grip on the hose's spiral rib without damaging the outer material. The body band is galvanised steel and the screw similarly. 19 dimensions with clamping range from 25 mm to 209 mm cover the AIRDUC series' main range. Typically used in pneumatic conveying installations where the bridge construction is critical for secure grip and electrical insulation.

## Technical specifications

<b>Material</b>	Body: galvanised steel. Bridge: PA6 Quality W1 (reinforced polyamide). Screw: galvanised steel
<b>Wall construction</b>	Bridge clamp with PA6 W1 plastic bridge and galvanised body
<b>Cut to length</b>	No
<b>Manufacturer SKU</b>	2100000

### Standards and compliance

REACH, RoHS

## Dimensions and ordering

The hose is supplied in 19 standard sizes from inner Ø 25.0 mm to 209.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Weight [kg/m]	Article no.
25	31	0.02	21000250000
32	39	0.025	21000320000
40	49	0.03	21000400000
50	59	0.03	21000500000
60	69	0.03	21000600000
70	79	0.03	21000700000
80	89	0.03	21000800000
90	99	0.03	21000900000
100	109	0.03	21001000000
110	119	0.03	21001100000
120	129	0.03	21001200000
130	139	0.03	21001300000
140	149	0.03	21001400000
150	159	0.03	21001500000
160	169	0.03	21001600000
170	179	0.03	21001700000
180	189	0.03	21001800000
190	199	0.03	21001900000
200	209	0.03	21002000000

The table shows the product's standard dimensions. Weight column is per piece.

## Other Particulair microsities

---

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

<a href="https://particulair.eu/ex-vac">particulair.eu/ex-vac</a>	ATEX and ACD vacuum cleaners for explosion hazard zones
<a href="https://particulair.eu/vace">particulair.eu/vace</a>	Nozzles and accessories for critical environments
<a href="https://particulair.eu/life-science">particulair.eu/life-science</a>	Vacuums for pharma and cleanroom
<a href="https://particulair.eu/hardo">particulair.eu/hardo</a>	Explosion-protected electrical Ex-equipment

## Contact and advisory

---

### Particulair

Højtoften 12  
2690 Karlslunde, Denmark  
CVR: 34129894

Phone: (+45) 70 23 12 03  
E-mail: [sales@particulair.com](mailto:sales@particulair.com)  
Web: [particulair.eu](https://particulair.eu)

**Product page:** [particulair.eu/flexcore/en/accessories/clamp-210-bridge/](https://particulair.eu/flexcore/en/accessories/clamp-210-bridge/)

---

### SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.