

## ACCESSORIES

# CLAMP 211

T-bolt clamp for heavy-duty hoses with smooth outer wall, quick to fit, reusable



CLAMP 211 is a T-bolt clamp developed for heavy-duty hoses with a smooth outer wall. The characteristic T-bolt construction provides quick mounting without special tools and allows the clamp to be reused multiple times without losing clamping force. The clamp is supplied in 34 dimensions with a clamping range from 17 mm to 280 mm, so every hose diameter in the AIRDUC PUR/PVC and PROTAPPE series can be paired with a suitable clamp. Typically used in industrial installations where the hose periodically must be detached - e.g. for cleaning, reconfiguration or servicing of pneumatic conveying lines.

## Technical specifications

<b>Wall construction</b>	T-bolt clamp with tightening bolt - quick to fit and reusable
<b>Cut to length</b>	No
<b>Manufacturer SKU</b>	2110000

### Standards and compliance

REACH, RoHS

## Dimensions and ordering

The hose is supplied in 34 standard sizes from inner Ø 17.0 mm to 280.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Weight [kg/m]	Article no.
17	19	0.37	21100210000
20	22	0.05	21100230000
23	25	0.05	21100250000
26	28	0.05	21100290000
29	31	0.09	21100310000
31	34	0.09	21100340000
36	39	0.09	21100400000
40	43	0.06	21100430000
44	47	0.09	21100470000
48	51	0.09	21100510000
52	55	0.07	21100550000
56	59	0.115	21100590000
60	63	0.07	21100630000
64	67	0.12	21100680000
68	73	0.15	21100730000
74	79	0.15	21100790000
80	85	0.15	21100850000
86	91	0.153	21100910000
92	97	0.17	21100970000
98	103	0.165	21101040000
104	112	0.1	21101120000
113	121	0.17	21101210000
122	130	0.182	21101300000
131	139	0.15	21101400000
140	148	0.18	21101500000
149	161	0.288	21101620000
162	174	0.19	21101740000
175	187	0.32	21101870000
188	200	0.32	21102000000
201	213	0.25	21102130000
214	226	0.25	21102260000
227	239	0.25	21102390000

Inner Ø [mm]	Outer Ø [mm]	Weight [kg/m]	Article no.
240	252	0.26	21102520000
270	280	0.11	21102800000

The table's 'inner diameter' columns show the clamp's clamping range (min - max). Choose a clamp where the hose's actual outer diameter falls within this range. The weight column is per piece.

## Other Particulair microsities

---

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

<a href="https://particulair.eu/ex-vac">particulair.eu/ex-vac</a>	ATEX and ACD vacuum cleaners for explosion hazard zones
<a href="https://particulair.eu/vace">particulair.eu/vace</a>	Nozzles and accessories for critical environments
<a href="https://particulair.eu/life-science">particulair.eu/life-science</a>	Vacuums for pharma and cleanroom
<a href="https://particulair.eu/hardo">particulair.eu/hardo</a>	Explosion-protected electrical Ex-equipment

## Contact and advisory

---

### Particulair

Højtoften 12  
2690 Karlslunde, Denmark  
CVR: 34129894

Phone: (+45) 70 23 12 03  
E-mail: [sales@particulair.com](mailto:sales@particulair.com)  
Web: [particulair.eu](https://particulair.eu)

**Product page:** [particulair.eu/flexcore/en/accessories/clamp-211/](https://particulair.eu/flexcore/en/accessories/clamp-211/)

---

### SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.