

ACCESSORIES

CONNECT 228 clamp protection tape

CONNECT 228 polyurethane clamp protection tape - chemical- and abrasion-resistant, high-temp 125 deg C



CONNECT 228 is an elastic polyurethane tape mounted between hose and clamp to protect the hose wall from local wear and crush damage. The tape is chemical-resistant, highly abrasion-resistant and temperature-resistant up to 125 deg C. Particularly valuable on heavy-duty installations where clamp tension could deform the hose.

Technical specifications

Material	Polyurethane (PUR), elastic
Wall construction	Protection tape between hose and clamp
Cut to length	No
Manufacturer SKU	2280000

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 50.0 mm to 100.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
50	0.03	2280050000
100	0.06	2280100000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particular microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/connect-228-clamp-protect/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.