

ACCESSORIES

CONNECT Tri-Clamp 245 svejse-stutsen

Tri-Clamp 245 socket for welding per DIN 32676 - for permanent integration in process tanks



Welding socket for Tri-Clamp 245 system per DIN 32676. The socket is welded directly onto process tank, valve or other process component to provide a permanent Tri-Clamp port. Material is stainless steel AISI 316L matching the fitting (5).

Technical specifications

Material	Stainless steel 1.4404 (= AISI 316L)
Wall construction	Tri-Clamp welding socket per DIN 32676
Cut to length	No
Manufacturer SKU	2458913

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 25.0 mm to 100.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
25	0.08	24500258913
50	0.19	24500508913
100	0.58	24501008913

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/connect-245-stutzen/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.