

ACCESSORIES

CONNECT ASEPTIC FITTING 249 DIN 11864-1

Aseptic hose adapter to DIN 11864-1, sealing form A, stainless steel 1.4404 (AISI 316L)



CONNECT ASEPTIC FITTING 249 in the DIN 11864-1 version is an aseptic hose adapter with sealing form A for screwed and flanged connections. The adapter is made of stainless steel 1.4404 (AISI 316L) with stamped marking and can be used from -40 to +90 °C. Available from DN 25 to DN 100.

Temp: -40°C to +90°C

Technical specifications

Material	Stainless steel 1.4404 (stamped) = AISI 316L
Wall construction	Aseptic screwed/flanged adapter, sealing form A
Temperature range	-40°C – +90°C
Cut to length	No
Manufacturer SKU	2492916

Standards and compliance

REACH, RoHS

Dimensions and ordering

The product is supplied in 7 standard sizes. Each size has its own article number.

Nom. width [mm]	Inner Ø [mm]	Weight [kg/pc.]	Article no.
25	26	0.1	24900252916
32	32	0.2	24900322916
40	38	0.51	24900402916
50	50	0.51	24900502916
65	66	1.45	24900652916
80	81	1.97	24900802916
100	100	-	24901002916

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/connect-249-din-11864-1/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.