

ACCESSORIES

3-vejs kugleventil type 129

3-way ball valve type 129 - alternative to type 128 with different configuration



Type 129 is an alternative configuration of the 3-way ball valve system (compare type 128, SKU 5280). The difference typically lies in material specification or bore configuration (L vs T). Cross-check factsheet when ordering.

Technical specifications

Material	Brass body, stainless ball, PTFE seal
Wall construction	3-way ball valve with L- or T-bore
Cut to length	No
Manufacturer SKU	5281

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 13.0 mm to 25.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Press. DIN [bar]	Weight [kg/m]	Article no.
13	30	0.44	5281013000
25	30	0.9	5281025000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/dreiwege-kugelhahn-129/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.