ACCESSORIES

Festflansch (fast flange)

Festflansch (fixed flange) - welded or built onto pipe end

Festflansch is a fixed flange that is welded or built onto the pipe end. In contrast to losflansch (5611) which can rotate freely, festflansch sits fixed in one orientation. Used where flange orientation is critical for correct bolt pattern or routing.

Technical specifications

Material	Galvanised or stainless steel
Wall construction	Fixed flange per DIN standard
Cut to length	No
Manufacturer SKU	5610

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 80.0 mm to 150.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
80	1.2	5610080000
100	1.85	5610100000
150	3.4	5610150000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair
Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/festflansch/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.