

## ABRASION-RESISTANT

# GOLDSCHLANGE

Robust EPDM water hose with CR outer layer - kink, impact and drive-over resistant



GOLDSCHLANGE is a heavy-duty water hose with EPDM lining and wrapped CR outer layer. The construction is kink, impact and drive-over resistant - relevant in agriculture, construction and industry where the hose is subjected to mechanical impacts and UV exposure. Wide temperature capacity (up to 100 C continuous, 130 C at steam cleaning) also makes it suitable for high-pressure and hygiene applications.

**Media:** Liquid

**Temp:** -30 °C to 100 °C

✓ Cut to length

## APPLICATIONS

- Irrigation and fertilizer systems in agriculture and horticulture
- Process water and cooling media distribution in industry
- Tank and asbestos cleaning with steam
- High-pressure cleaning and car washing
- Injection moulding cooling circuits
- Roof drainage and rainwater systems

## Technical specifications

<b>Material</b>	EPDM inner lining, CR (chloroprene rubber) wrapped outer wall
<b>Colour</b>	black
<b>Wall construction</b>	Wrap outer wall (CR), smooth EPDM lining with textile plies
<b>Conveying media</b>	Liquid
<b>Temperature range</b>	-30 °C – 100 °C
<b>Short-term peak</b>	130 °C
<b>Cut to length</b>	Yes
<b>Manufacturer SKU</b>	3026

### Standards and compliance

en-iso-1307, REACH, RoHS

## Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 13.0 mm to 25.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Wall th. [mm]	Press. DIN [bar]	Bend rad. [mm]	Max len. [m]	Weight [kg/m]	Roll [m]	Article no.
13	20.8	3.9	30	50	40	0.225	40	3026013000
19	27.8	4.4	25	80	40	0.385	40	3026019000
25	34	4.5	20	160	40	0.49	40	3026025000

Fields without a value (—) are not specified in the manufacturer's factsheet. Overpressure and underpressure values are recommended operating limits; the product can be subjected to higher loads on request. Bend radius is measured along the inside of the hose bend.

## Other Particulair microsities

---

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

<a href="https://particulair.eu/ex-vac">particulair.eu/ex-vac</a>	ATEX and ACD vacuum cleaners for explosion hazard zones
<a href="https://particulair.eu/vace">particulair.eu/vace</a>	Nozzles and accessories for critical environments
<a href="https://particulair.eu/life-science">particulair.eu/life-science</a>	Vacuums for pharma and cleanroom
<a href="https://particulair.eu/hardo">particulair.eu/hardo</a>	Explosion-protected electrical Ex-equipment

## Contact and advisory

---

### Particulair

Højtoften 12  
2690 Karlslunde, Denmark  
CVR: 34129894

Phone: (+45) 70 23 12 03  
E-mail: [sales@particulair.com](mailto:sales@particulair.com)  
Web: [particulair.eu](https://particulair.eu)

**Product page:** [particulair.eu/flexcore/en/abrasive/goldschlange/](https://particulair.eu/flexcore/en/abrasive/goldschlange/)

---

### SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.