

ACCESSORIES

Hoejtryks-damp-slange-kobling

High-pressure steam hose coupling - for strong-steam installations above BOSS system level



High-pressure steam hose coupling is developed for strong-steam installations where the BOSS system level (210 deg C) is insufficient. Construction is reinforced galvanised or cast steel with special seals for 250+ deg C. Used in heavy process and brewery applications.

Technical specifications

Material	Galvanised/cast steel reinforced
Wall construction	High-pressure steam coupling
Cut to length	No
Manufacturer SKU	5431

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 25.0 mm to 50.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
25	0.42	5431025000
50	1.18	5431050000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac ATEX and ACD vacuum cleaners for explosion hazard zones

particulair.eu/vace Nozzles and accessories for critical environments

particulair.eu/life-science Vacuums for pharma and cleanroom

particulair.eu/hardo Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/hochdruck-dampfkupplung/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.