

CHEMICAL-RESISTANT

INDUCORD Lancia

Marine mooring and bunkering pressure hose



INDUCORD Lancia is specialised for marine mooring and bunkering applications. Resistant to seawater, fire-resistant per ISO 7840 and certified for marine fuel.

Media: Liquid, Gas

Temp: -30 °C to 80 °C

✓ Cut to length

APPLICATIONS

- Chemical and solvent transport
- Oil and petrol distribution
- Mooring and bunkering in shipping
- Metal casting and heat handling
- Compressed air and air supply
- Water and slurry transport
- Industrial spraying

Technical specifications

Material	Rubber with steel-wire reinforcement
Colour	black
Wall construction	Rubber with steel-wire reinforcement with reinforcement
Spiral material	Textile / steel reinforcement
Conveying media	Liquid, Gas
Temperature range	-30 °C – 80 °C
Short-term peak	80 °C
Cut to length	Yes
Manufacturer SKU	3770

Standards and compliance

en-12115, en-iso-1307, REACH, RoHS, iso-7840, en-1761

Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 25.0 mm to 38.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Wall th. [mm]	Press. DIN [bar]	Burst [bar]	Max len. [m]	Weight [kg/m]	Roll [m]	Article no.
25	35	5	10	30	15	0.64	15	3043025000
32	44	6	10	30	15	0.95	15	3043032000
38	50	6	10	30	25	1.11	25	3043038000

Fields without a value (em-dash) are not specified in the manufacturer's factsheet. Pressure values are recommended operating limits. Bend radius is measured along the inside of the hose bend.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/chemical/inducord-lancia/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.