

ACCESSORIES

Klau-kobling variant (SKU 5219)

Claw coupling variant SKU 5219 - DIN 3489, malleable cast iron



Claw coupling variant SKU 5219 per DIN 3489. Difference from canonical 5212 is likely thread size or hose tail configuration. Lug distance is constant 42 mm.

Technical specifications

Material	Malleable cast iron, NBR
Wall construction	Claw coupling variant SKU 5219
Cut to length	No
Manufacturer SKU	5219

Standards and compliance

din-3489, din-en-iso-228-1, REACH, RoHS

Dimensions and ordering

The hose is supplied in 1 standard sizes from inner Ø 42.0 mm to 42.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Press. DIN [bar]	Weight [kg/m]	Article no.
42	10	0.15	5219010000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac ATEX and ACD vacuum cleaners for explosion hazard zones

particulair.eu/vace Nozzles and accessories for critical environments

particulair.eu/life-science Vacuums for pharma and cleanroom

particulair.eu/hardo Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/klauen-5219/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.