

ACCESSORIES

Losflansch (loose flange)

Losflansch (swiveling flange) - can rotate freely around pipe end for easy bolt pattern alignment



Losflansch is a loose flange that can rotate freely around the pipe end. This is a major advantage when retrofitting on existing installations where the mating flange's bolt pattern must be aligned with the pipe orientation - a fixed flange would require rotating the entire pipe connection. Losflansch solves the problem by just rotating the flange.

Technical specifications

Material	Galvanised or stainless steel
Wall construction	Loose flange with free rotation
Cut to length	No
Manufacturer SKU	5611

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 80.0 mm to 150.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
80	1.1	5611080000
100	1.7	5611100000
150	3.1	5611150000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/losflansch/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.