ACCESSORIES

Dairy coupling cap

Cap with female thread to DIN 11851 for closing a VMS part, stainless steel with NBR seal

Cap for dairy couplings to DIN 11851. The cap has a female round thread (DIN 405-1) and is screwed onto a part with male thread, such as a VMS part, when the line is to be closed. The cap is made of stainless steel 1.4301 with a beige NBR seal. Available from DN 25 to DN 100.

Technical specifications

Material	Stainless steel 1.4301; NBR seal
Colour	Seal beige
Wall construction	Cap with female round thread
Cut to length	No
Manufacturer SKU	5543

Standards and compliance

din-11851

Dimensions and ordering

The product is supplied in 7 standard sizes. Each size has its own article number.

Nom. width [mm]	Outer Ø [mm]	Thread	Weight [kg/pc.]	Article no.
25	63	Rd 52 x 1/6"	0.217	5543025000
32	70	Rd 58 x 1/6"	0.242	5543032000
40	78	Rd 65 x 1/6"	0.299	5543038000
50	92	Rd 78 x 1/6"	0.434	5543050000
65	112	Rd 95 x 1/6"	0.725	5543063000
80	127	Rd 110 x 1/4"	0.975	5543075000
100	148	Rd 130 x 1/4"	1.424	5543100000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair
Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/mejerikobling-daeksel/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.