

HIGH-TEMPERATURE

NEO 390 ONE

Single-layered neoprene hose for hot and cold gases up to 150 C



NEO 390 ONE is the single-layered neoprene hose for hot and cold gases. Highly flexible and heat-resistant up to 150 C, ideal for hot-air drying, cooling and air conditioning in the automotive industry.

Media: Gas

Temp: -40 °C to 150 °C

✓ Cut to length

APPLICATIONS

- NEO 390 ONE-typical industrial application
- Highly flexible connection
- Compressed air and media transport
- Industrial process coupling
- Continuous operation
- High flexibility in compact spaces
- Robust mechanical load

Technical specifications

Material	Neoprene (CR rubber)
Colour	black
Wall construction	Neoprene (CR rubber) with reinforcement
Spiral material	Forstaerkning
Conveying media	Gas
Temperature range	-40 °C – 150 °C
Short-term peak	150 °C
Cut to length	Yes
Manufacturer SKU	3900000

Standards and compliance

en-iso-1307, REACH, RoHS

Dimensions and ordering

The hose is supplied in 31 standard sizes from inner Ø 13.0 mm to 305.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Press. DIN [bar]	Vacuum axial [bar]	Bend rad. [mm]	Max len. [m]	Weight [kg/m]	Roll [m]	Article no.
13	15	1.8	0.58	9	4	0.05	4	39000130000
19	21	1.8	0.58	12	4	0.08	4	39000190000
22	24	1.8	0.58	13	4	0.09	4	39000220000
25	29	1.5	0.58	17	4	0.12	4	39000250000
32	35	1.5	0.58	19	4	0.13	4	39000320000
38	42	1.5	0.58	23	4	0.17	4	39000380000
41	45	1.5	0.57	25	4	0.18	-	39000410000
45	48	1.5	0.56	26	4	0.19	4	39000440000
51	55	1.5	0.5	30	4	0.25	4	39000510000
55	59	1.3	0.5	32	12	0.27	-	39000550000
57	61	1.3	0.5	33	4	0.28	4	39000570000
65	67	1.3	0.5	36	4	0.3	4	39000630000
70	74	1.2	0.5	39	4	0.4	4	39000700000
76	80	1.1	0.39	42	4	0.41	4	39000760000
80	84	1.1	0.39	44	4	0.43	4	39000800000
83	87	1.1	0.39	46	4	0.47	4	39000830000
90	93	1.1	0.38	49	4	0.5	4	39000890000
95	99	1.1	0.38	52	4	0.54	4	39000950000
102	106	1.1	0.3	55	4	0.57	4	39001020000
108	113	1	0.3	59	4	0.68	4	39001080000
114	119	1	0.3	62	4	0.73	4	39001140000
121	126	0.9	0.29	66	4	0.76	4	39001210000
127	132	0.9	0.21	69	4	0.81	4	39001270000
140	145	0.9	0.2	75	4	0.89	4	39001400000
152	157	0.8	0.18	81	4	1.05	4	39001520000
160	165	0.7	0.16	85	4	1.1	-	39001600000
165	170	0.7	0.15	88	4	1.15	-	39001650000
180	183	0.6	0.14	94	4	1.21	4	39001780000
203	208	0.6	0.1	107	4	1.38	4	39002030000
254	259	0.4	0.1	132	4	1.65	4	39002540000
305	310	0.1	0.07	158	4	2	4	39003050000

Fields without a value are not specified in the manufacturer's factsheet. Pressure values are recommended operating limits. Bend radius is measured along the inside of the hose bend.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/high-temperature/neo-390-one/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.