

FLAME-RETARDANT

NORDUC PA 134

Black, liquid-tight PA6 protection hose for cables in electrical and switch cabinet installations



Corrugated protection hose made of PA6. Highly flexible and liquid-tight, black. Intended for cable protection in electrical and switch cabinet installations and in switchgear construction. Service from -40°C to $+125^{\circ}\text{C}$, IP 68 to EN/IEC 60529 and flame-retardant to UL94-HB.

Temp: -40°C to $+125^{\circ}\text{C}$

✓ Cut to length

APPLICATIONS

- Cable protection in electrical installations
- Cable protection in switch cabinets
- Switchgear construction
- Cable routing on machines and welding robots

Technical specifications

Material	PA6 (polyamide 6), corrugated
Colour	Black
Wall construction	Corrugated wall, liquid-tight
Temperature range	-40°C – +125°C
Short-term peak	+125°C
Cut to length	Yes
Manufacturer SKU	1349050

Standards and compliance

UL94-HB (fire), en-iec-60529-ip68

Dimensions and ordering

The hose is supplied in 8 standard sizes from inner Ø 8.4 mm to 47.7 mm. Each size has its own article number. Standard roll lengths are 25, 50 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Bend rad. [mm]	Max len. [m]	Weight [kg/m]	Roll [m]	Article no.
8.4	11.7	15	50	0.024	50	13430129050
9.9	13	20	50	0.025	50	13430139050
12.7	15.8	35	50	0.037	50	13430169050
16.6	21.2	45	50	0.055	50	13430219050
23.2	28.3	55	50	0.09	50	13430289050
29	34.5	65	25	0.1252	25	13430359025
36	42.4	90	25	0.172	25	13430429025
47.7	54	100	25	0.224	25	13430549025

Fields without a value (—) are not specified in the manufacturer's factsheet. Overpressure and underpressure values are recommended operating limits; the product can be subjected to higher loads on request. Bend radius is measured along the inside of the hose bend.

Other Particulair microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/flame-retardant-hoses/norduc-pa-134/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.