

ABRASION-RESISTANT

NORFLEX® PUR 401, scraping hose

PUR scraping hose, 8 bar, -25 to +90°C



NORFLEX® PUR 401, scraping hose is a PUR hose with a 2.2 mm wall. The manufacturer states a working pressure of 8 bar and a normal temperature range from -25 to +90°C, short-term up to +125°C. The hose is supplied in inner Ø 11.6 mm in lengths up to 50 m.

Temp: -25°C to +90°C

✓ Cut to length

APPLICATIONS

- Scraping hose

Technical specifications

Material	PUR
Colour	Transparent
Wall construction	Wall thickness 2.2 mm
Temperature range	-25°C – +90°C
Short-term peak	+125°C
Cut to length	Yes
Manufacturer SKU	4015350

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 1 standard sizes from inner Ø 11.6 mm to 11.6 mm. Each size has its own article number.

Inner Ø [mm]	Outer Ø [mm]	Wall th. [mm]	Press. DIN [bar]	Bend rad. [mm]	Max len. [m]	Weight [kg/m]	Article no.
11.6	18.2	2.2	8	64	50	0.19	40191165350

Fields without a value (—) are not specified in the manufacturer's factsheet. Overpressure and underpressure values are recommended operating limits; the product can be subjected to higher loads on request. Bend radius is measured along the inside of the hose bend.

Other Particulair microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/abrasion-resistant-hoses/norflex-pur-401-scraping-hose/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.