

ABRASION-RESISTANT

NORFLEX® PUR 441 ROBOTIC BLUE

Abrasion-resistant PUR high-pressure hose for robotics — Blue, up to 20 bar working pressure



Abrasion-resistant high-pressure hose in polyurethane, fabric-reinforced with polyester reinforcement. Designed specifically for industrial robots, where the hose must follow the robot arm's movements cycle after cycle without abrading or kinking. Working pressure up to 20 bar, burst pressure up to 80 bar. Service from -35 °C to $+80\text{ °C}$. The blue colour provides visual separation between multiple parallel hoses on the same robot — e.g. different colours for compressed air, coolant and hydraulics.

Media: Liquid, Gas

Temp: -35 °C to 80 °C

✓ Cut to length

APPLICATIONS

- Compressed air supply to robot grippers
- Coolant transport on robot arm
- Hydraulic connections on industrial robots
- Water supply on automated machines
- Industrial pneumatic installations
- Cooling water in process cooling

Technical specifications

Material	Polyurethane (PUR), polyester reinforcement, blue outer layer
Colour	Blue
Wall construction	Smooth interior + exterior, extruded, polyester reinforcement
Spiral material	polyester plies
Conveying media	Liquid, Gas
Temperature range	-35 °C – 80 °C
Short-term peak	80 °C
Cut to length	Yes
Manufacturer SKU	4410400

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 4 standard sizes from inner Ø 6.4 mm to 19.5 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Wall th. [mm]	Press. DIN [bar]	Burst [bar]	Bend rad. [mm]	Max len. [m]	Weight [kg/m]	Roll [m]	Article no.
6.4	12.7	3.15	20	80	22	50	0.13	50	44190640400
9.4	16	3.3	20	80	55	100	0.149	50	44190940400
12.5	19.5	3.5	20	80	69	100	0.24	50	44191280400
19.5	28.5	4.5	20	50	140	50	0.44	50	44191900400

Fields without a value (—) are not specified in the manufacturer's factsheet. Overpressure and underpressure values are recommended operating limits; the product can be subjected to higher loads on request. Bend radius is measured along the inside of the hose bend.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/abrasive/norflex-pur-441-robotic-blue/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.