

HIGH-TEMPERATURE

NORFLEX SIL 408 special wall 2.5 mm

High-temperature food-grade silicone 2.5 mm wall, -60 to +180 C



NORFLEX SIL 408 special wall 2.5 mm is a high-temperature food-grade silicone hose with 2.5 mm wall. The hose is crush-resistant and highly flexible, and the operating range -60 to +180 C makes it suitable for food and pharma applications with high temperatures - incl. steam cleaning (SIP), beverage filling and hose pump applications. The transparent wall allows visual inspection. NORFLEX SIL 408 is available in multiple wall variants (1.5, 2, 2.5 and 3 mm) for different pressure and flexibility needs.

Media: Liquid, Gas

Temp: -60 °C to 180 °C

✓ Cut to length

APPLICATIONS

- Food process installations with steam CIP cleaning
- Pharma SIP (Sterilisation In Place) at up to +180 C
- Beverage filling with heat cycles
- Dairy process intensity and milk treatment
- Hose pump applications with hot media
- Tablet press and pharma bulk handling

Technical specifications

Material	Food-grade silicone
Colour	transparent
Wall construction	Smooth inner/outer 2.5 mm silicone wall, smooth construction cover
Spiral material	(ingen spiral - silikone-vaeg konstruktion)
Conveying media	Liquid, Gas
Temperature range	-60 °C – 180 °C
Short-term peak	180 °C
Cut to length	Yes
Manufacturer SKU	4082174

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 1 standard sizes from inner Ø 10.0 mm to 10.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Wall th. [mm]	Max len. [m]	Weight [kg/m]	Roll [m]	Article no.
10	15	2.5	50	0.11	50	40891002174

Fields without a value (—) are not specified in the manufacturer's factsheet. Overpressure and underpressure values are recommended operating limits; the product can be subjected to higher loads on request. Bend radius is measured along the inside of the hose bend.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/high-temperature/norflex-sil-408-special-wall-2-5-mm/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.