

ACCESSORIES

Trykluft-stiknippel DN 5,5

Compressed air nipple DN 5.5 - male side for quick coupling DN 5.5 (5235)



The plug nipple is the male side of the compressed air quick coupling system. The DN 5.5 nipple is inserted into the coupling's (5235) female port and locks via push-fit or screw mechanism. For complete system, order both coupling (5235) and nipple (this 5233) in matching configuration.

Technical specifications

Material	Galvanised steel / brass
Wall construction	Compressed air male nipple DN 5.5
Cut to length	No
Manufacturer SKU	5233

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 5.5 mm to 5.5 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Press. DIN [bar]	Weight [kg/m]	Article no.
5.5	12	0.03	5233055000
5.5	12	0.038	5233055001

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac ATEX and ACD vacuum cleaners for explosion hazard zones

particulair.eu/vace Nozzles and accessories for critical environments

particulair.eu/life-science Vacuums for pharma and cleanroom

particulair.eu/hardo Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/pressluftnippel-dn55/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.