

ACCESSORIES

PTFE-tape

PTFE tape (Teflon tape) - for sealing thread pipe connections



PTFE tape (Teflon tape) is a white plastic tape of polytetrafluoroethylene wrapped around threads for a leak-free joint. Widely used for water, gas and air installations. Resistant to nearly all chemicals and high temperatures (-200 to +260 deg C).

Temp: -200.0 °C to 260.0 °C

Technical specifications

Material	Polytetrafluoroethylene (PTFE/Teflon)
Colour	white
Wall construction	PTFE plastic sealing tape
Temperature range	-200.0 °C – 260.0 °C
Cut to length	No
Manufacturer SKU	7500

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 12.0 mm to 19.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
12	0.02	7500012000
19	0.03	7500019000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/ptfe-tape/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.