

ACCESSORIES

Slangeklemme med sikkerheds-klauer

Hose clamp with 2 safety claws - mechanical anti-blow-off on high-pressure installations



Hose clamp with safety claws combines standard screw tensioning with 2 mechanical claws gripping into the hose wall. This provides secondary anti-blow-off securing under high-pressure impulses or thermal expansion. Typically used in industrial compressed air, steam and hydraulics installations where a smooth screw clamp alone is insufficient.

Technical specifications

Material	Galvanised steel
Wall construction	Clamp with 2 safety claws + screw tensioning
Cut to length	No
Manufacturer SKU	6305

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 20.0 mm to 120.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Outer Ø [mm]	Weight [kg/m]	Article no.
20	30	0.04	6305020030
50	70	0.085	6305050070
100	120	0.145	6305100120

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/schlauchklemme-sicherungsklaeu/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.