

ACCESSORIES

TW form-pakning Viton

TW form-shaped sealing in Viton (FKM) for MKV sealing rings - high-temperature and chemical-resistant



TW form-shaped seal is manufactured from Viton (FKM - Fluoroelastomer) which is a high-performance sealing material with exceptional high-temperature resistance and broad chemical resistance. Used specifically for MKV (crown ring) sealing applications in the TW system where temperature and chemical exposure are challenging.

Technical specifications

Material	Viton (FKM - Fluoroelastomer)
Wall construction	TW form seal Viton for MKV
Cut to length	No
Manufacturer SKU	5036

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 50.0 mm to 80.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
50	0.013	5037050000
80	0.028	5037075000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac ATEX and ACD vacuum cleaners for explosion hazard zones

particulair.eu/vace Nozzles and accessories for critical environments

particulair.eu/life-science Vacuums for pharma and cleanroom

particulair.eu/hardo Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/tw-formdichtning/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.