

## ACCESSORIES

## TW gevind-pakning

TW thread seal - for BSPP threads on TW couplings, NBR or silicone



Thread seal specifically for the TW system's BSPP/G thread connections. The seal's geometry matches the TW coupling's thread face and provides a correct seal between male and female threads. Sold as spare part.

## Technical specifications

<b>Material</b>	NBR or silicone
<b>Wall construction</b>	TW thread seal
<b>Cut to length</b>	No
<b>Manufacturer SKU</b>	5582

### Standards and compliance

REACH, RoHS

## Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 50.0 mm to 80.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
50	0.008	5582050000
80	0.018	5582075000

The table shows the product's standard dimensions. Weight column is per piece.

## Other Particulair microsities

---

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

<a href="https://particulair.eu/ex-vac">particulair.eu/ex-vac</a>	ATEX and ACD vacuum cleaners for explosion hazard zones
<a href="https://particulair.eu/vace">particulair.eu/vace</a>	Nozzles and accessories for critical environments
<a href="https://particulair.eu/life-science">particulair.eu/life-science</a>	Vacuums for pharma and cleanroom
<a href="https://particulair.eu/hardo">particulair.eu/hardo</a>	Explosion-protected electrical Ex-equipment

## Contact and advisory

---

### Particulair

Højtoften 12  
2690 Karlslunde, Denmark  
CVR: 34129894

Phone: (+45) 70 23 12 03  
E-mail: [sales@particulair.com](mailto:sales@particulair.com)  
Web: [particulair.eu](https://particulair.eu)

**Product page:** [particulair.eu/flexcore/en/accessories/tw-gewindedichtning/](https://particulair.eu/flexcore/en/accessories/tw-gewindedichtning/)

---

### SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.