

ACCESSORIES

TW kobling type VK

TW coupling type VK in stainless steel with BSPP female thread - 16 bar working pressure



TW coupling type VK is a variant of the TW coupling system with BSPP/G female thread and a simpler construction than MK type. The material is stainless steel with 16 bar working pressure. Three standard sizes (VK 50, 80, 100) cover the bulk of the tank truck installation range. Typically used in less critical TW applications where the MK type's dual-ring construction is not required.

Technical specifications

Material	Stainless steel
Wall construction	TW VK coupling with BSPP/G female thread
Cut to length	No
Manufacturer SKU	5573

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 3 standard sizes from inner Ø 50.0 mm to 100.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Press. DIN [bar]	Weight [kg/m]	Article no.
50	16	0.291	5562050050
80	16	0.675	5562075075
100	16	1.114	5562100100

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/tw-kupplung-vk/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.