

ACCESSORIES

TW slange-stutsen male

TW hose coupling male - male side hose tail for TW installations



Male side hose tail for the TW system. The hose is pushed onto the stutsen and fastened with clamp; the male side is then connected to TW female coupling (5538). Standard stainless steel construction.

Technical specifications

Material	Stainless steel
Wall construction	TW male hose tail
Cut to length	No
Manufacturer SKU	5537

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 50.0 mm to 80.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
50	0.35	5537050050
80	0.72	5537075075

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsities

We build specialised microsities for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair

Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/tw-schlauchstutzen-male/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.