ACCESSORIES

TW prop type VB

TW plug type VB in polyamide with chain hole - for clamping ring MKV and MK couplings

TW plug type VB is developed to close an open TW MK coupling or clamping ring MKV. Material is polyamide (PA) - a thermoplastic construction weighing significantly less than metal alternatives. Includes chain hole for safety chain.

Technical specifications

Material	Polyamide (PA)
Wall construction	TW plug VB with chain hole, polyamide
Cut to length	No
Manufacturer SKU	5564

Standards and compliance

REACH, RoHS

Dimensions and ordering

The hose is supplied in 2 standard sizes from inner Ø 50.0 mm to 80.0 mm. Each size has its own article number. Standard roll length is typically 10 m, and the hose can be cut to length.

Inner Ø [mm]	Weight [kg/m]	Article no.
50	0.045	5565050000
80	0.104	5565075000

The table shows the product's standard dimensions. Weight column is per piece.

Other Particulair microsites

We build specialised microsites for critical industries. Each site provides in-depth product data, documentation and expert guidance for the domain it covers.

particulair.eu/ex-vac	ATEX and ACD vacuum cleaners for explosion hazard zones
particulair.eu/vace	Nozzles and accessories for critical environments
particulair.eu/life-science	Vacuums for pharma and cleanroom
particulair.eu/hardo	Explosion-protected electrical Ex-equipment

Contact and advisory

Particulair
Højtoften 12
2690 Karlslunde, Denmark
CVR: 34129894

Phone: (+45) 70 23 12 03
E-mail: sales@particulair.com
Web: particulair.eu

Product page: particulair.eu/flexcore/en/accessories/tw-stopfen-vb/

SMARTER THINKING • BETTER WORKING

This datasheet is generated automatically from Particulair product data. All specifications are taken from the manufacturer's factsheet and are subject to change without notice. Prices and availability provided on request.